

Carabiners > Specs

CARABINER SPECIFICATIONS

Find the right carabiner that meets all of your work and rescue specifications.

ALUMINUM CARABINERS

Name	Type	Length	Gate Opening	Weight	Breaking Strength
PMI Mate HMS	Screw gate	4"6 (116mm)	1" (25.4 mm)	3.2 oz (91 g)	24 kN (5,395 lbf)
PMI Mate Triplock	Autolock	4.6" (116 mm)	1" (25.4 mm)	3.2 oz (91 g)	24 kN (5,395 lbf)
SMC Large D	Screw Gate	5.04" (111.6 mm)	1.20" (30.5 mm)	3.8 oz (108 g)	34 kN (7,643 lbf)
SMC Locking D	Screw Gate	4.37" (111 mm)	0.82" (20.8 mm)	2.6 oz (76.3 g)	27 kN (6,070 lbf)
SMC Mountain D	Non-Locking	4.37" (111 mm)	0.95" (24 mm)	2.4 oz (70.4 g)	27 kN (6,592 lbf)
SMC Lightweight D	Non-Locking	3.96" (100 mm)	0.74" (20.8 mm)	2.6 oz (76.3 g)	20 kN (4,496 lbf)
SMC Oval	Non-Locking	4.27" (108 mm)	0.72" (18 mm)	2.2 oz (63 g)	20 kN (4,496 lbf)

STEEL CARABINERS

Name	Type	Length	Gate Opening	Weight	Breaking Strength	Certifications
SMC Autolocking	Autolocking	4.52" (145 mm)	2.76" (70 mm)	7.2 oz (204 g)	46 kN (10,341 lbf)	NFPA 1983 (2006 ED) "G"
Gator Steel	Autolocking	4.9" (125 mm)	0.9" (23 mm)	10.1 oz (285 g)	40 kN (9,000 lbf)	EN 362
SMC Large Safety Lock	Autolocking	5.0" (128 mm)	1.2" (31 mm)	11.3 oz (320 g)	46 kN (10,341 lbf)	
SMC Large	Screw Gate	5.04" (128 mm)	1.20" (30.5 mm)	10.6 oz (301 g)	46 kN (10,341 lbf)	NFPA 1983 (2006 ED) "G"
SMC X-Large	Screw Gate	5.70" (143 mm)	1.45" (36 mm)	12.2 oz (346 g)	54 kN (12,139 lbf)	NFPA 1983 (2006 ED) "G"
SMC Lite 67	Screw Gate	4.52" (145 mm)	0.94" (23.8 mm)	6.6 oz (194 g)	46 kN (10,341 lbf)	NFPA 1983 (2006 ED) "G"

Pigeon Mountain Industries, Inc.
PO Box 803
LaFayette, GA 30728

T: 800.282.7673
F: 706.764.1437
E: custserv@pmirope.com
W: www.pmirope.com